

Taller ESP8266

El contenido es:

1. ¿Qué es el ESP8266?
2. ¿Cómo se programa? (Explicación de las diferentes formas para programarlo y configuración del IDE de Arduino para hacerlo)
3. Montaje de un programador para el ESP-12
4. Ejemplo LED-Blink (Y de ahí lo que se les ocurra)

Materiales

- cable usb-mini (AGREGAR IMAGEN)
- ftdi (AGREGAR IMAGEN)
- protoboard (AGREGAR IMAGEN)
- soldador (AGREGAR IMAGEN)
- un computador con arduino instalado (AGREGAR IMAGEN)
- ESP12 (AGREGAR IMAGEN)
- pcb para ESP12 (AGREGAR IMAGEN)
- Suiche on/off de 6 patas (AGREGAR IMAGEN)
- Pulsador (AGREGAR IMAGEN)

1. ¿Qué es el ESP8266?

<http://espressif.com/products/hardware/esp8266ex/overview>

High Integrated

ESP8266EX is among the most integrated WiFi chips in the industry with the size of 5mm x 5mm ; it integrates the antenna switches, RF balun, power amplifier, low noise receive amplifier, filters, power management modules while requires minimal external circuitry. The entire solution, including front-end module, is designed to occupy minimal PCB area.

32-bit MCU

ESP8266EX integrates Tensilica L106 32-bit micro controller (MCU) which features extra low power consumption and 16-bit RSIC. The CPU clock speed is 80 MHz. It can also reach a maximum value of 160 MHz. Real Time Operation System (RTOS) is enabled. Currently, only 20% of MIPS has been occupied by the Wi-Fi stack, the rest can all be used for user application programming and development.

Low Power

ESP8266EX has been designed for mobile, wearable electronics and Internet of Things applications with the aim of achieving the lowest power consumption with a combination of several proprietary technologies. The power saving architecture operates in 3 modes: active mode, sleep mode and deep

sleep mode.

Robustness

By integrating more components on-chip, we have made the solution to be the most robust and manufacturable. Our solutions also feature the widest operating temperature range, from -40°C to +125°C.

<https://github.com/esp8266/esp8266-wiki/wiki>

What is this ESP8266

It's a wireless SoC
It has GPIO, I2C, ADC, SPI, PWM and some more
It's running at 80MHz
64KBytes of instruction RAM
96KBytes of data RAM
64KBytes boot ROM
It has a Winbond W25Q40BVNIG SPI flash
It's a RISC architecture
The core is a 106micro Diamond Standard core (LX3) made by Tensilica
The ESP8266 chip is made by Espressif
Modules bearing this chip are made by various manufacturers

Features

802.11 b/g/n protocol
Wi-Fi 2.4 GHz, support WPA/WPA2
Super small module size (11.5mm x 11.5mm)
Integrated 10-bit ADC
Integrated TCP/IP protocol stack (ipv4 only at the moment)
Integrated TR switch, balun, LNA, power amplifier and matching network
Integrated PLL, regulators, and power management units
+20dBm output power in 802.11b mode
Supports antenna diversity
Deep sleep power <10uA, Power down leakage current < 5uA
Integrated low power 32-bit MCU
SDIO 2.0, SPI, UART, I2C
STBC, 1x1 MIMO, 2x1 MIMO
A-MPDU & A-MSDU aggregation & 0.4μs guard interval
Wake up and transmit packets in < 2ms
Standby power consumption of < 1.0mW (DTIM3)
Operating temperature range -40C ~ 125C

Status API Training Shop Blog About Pricing

2. ¿Cómo se programa?

Arduino

Installing with Boards Manager

Starting with 1.6.4, Arduino allows installation of third-party platform packages using Boards Manager. We have packages available for Windows, Mac OS, and Linux (32 and 64 bit).

Install Arduino 1.6.5 from the Arduino website.

Start Arduino and open Preferences window.

Enter http://arduino.esp8266.com/stable/package_esp8266com_index.json into Additional Board Manager URLs field. You can add multiple URLs, separating them with commas.

Open Boards Manager from Tools > Board menu and install esp8266 platform (and don't forget to select your ESP8266 board from Tools > Board menu after installation).

The best place to ask questions related to this core is ESP8266 community forum:

<http://www.esp8266.com/arduino>. If you find this forum or the ESP8266 Boards Manager package useful, please consider supporting it with a donation. Donate

NodeMCU - LUA


MicroPython - Python

Smart.js - Javascript

Sming - C

3. Montaje de un programador para el ESP-12





4. Ejemplo LED-Blink (Y de ahí lo que se les ocurra)

```
#define LED_BUILTIN 2  
gpio15 no se desconecta de tierra
```

From:
<https://wiki.unloquer.org/> -



Permanent link:
<https://wiki.unloquer.org/documentacion-proceso/tecnologicos/taller-esp8266?rev=1457585465>

Last update: **2016/03/10 04:51**